

Comfort  
you can  
**count on,**  
all summer  
long.



**CONCORD**  
Quality heating and cooling products

# Cool comfort for your entire home.

## SAVE ENERGY, SAVE MONEY

Our air conditioners have a 13 SEER rating to provide exceptional cooling performance. They are designed to help you use significantly less energy than units installed as recently as five years ago.

## MAKE YOURSELF COMFORTABLE

Concord air conditioners quietly cool your home for the ultimate comfort. Copeland® compressors have fewer moving parts for dependable, quiet operation, while the precision-balanced direct drive fan sends hot air and noise up and away from your home. The cabinet easily blends with most architecture and landscaping.

## BUILT TO LAST

Attractive louvered panels protect coils and are easy to service, while the compressors are designed for reliable and efficient money-saving performance. Factory-installed liquid line filter driers protect the compressors from contaminants. The corrosion-resistant cabinet is built from strong, heavy-gauge prepainted steel and has drain holes to quickly remove standing water from the base pan before corrosion can start.

## RUGGED AND RELIABLE

Every Concord 2AC13 unit is tested for leaks and proper operation at the factory to ensure faultless performance when you get it home. Each unit is backed with a 5-year limited parts warranty and a 5-year limited compressor warranty.

## UNIT DIMENSIONS

MODEL NUMBER	SQUARE BASE (INCHES)	HEIGHT (INCHES)	SEER	NOMINAL CAPACITY (TONS)
2AC13B18P/ 2AC13L18P	22-1/2	30-3/4	13.0	1.5
2AC13B24P/ 2AC13L24P	22-1/2	34-3/4	13.0	2.0
2AC13B30P/ 2AC13L30P	30	34-3/4	13.0	2.5
2AC13B36P/ 2AC13L36P, T	30	38-3/4	13.0	3.0
2AC13B42P/ 2AC13L42P	30	38-3/4	13.0	3.5
2AC13B48P/ 2AC13L48P, T	30	30-3/4	13.0	4.0
2AC13B60P/ 2AC13L60P, T	30	34-3/4	13.0	5.0

B=Non-louvered units; L=Metal louvered units  
T = 208-230V/60Hz/3 Phase models



- 13 SEER or up to 14 SEER when matched with a variable speed indoor section
- 1-1/2–5 tons nominal capacity
- Quiet, durable Copeland® compressor is safeguarded by internal pressure relief valves and inherent thermal protection
- Two coil guard protection options available
  - Louvered panels provide full metal coil guard (“L models”)
  - Naltex® Hail Guard™ protects from fin damage (“B models”)
- High-quality condenser coils use copper tubes with enhanced louvered fins for maximum heat transfer capability
- Permanently lubricated condenser fan motor needs no annual maintenance
- Vertical air discharge sends hot air up and away from home and shrubbery
- 5-year limited warranty on compressor and 5-year limited warranty on parts
- Designed with ease of service in mind featuring a hinged control panel for simple access to internal components
- Angled service valves are positioned to allow easy access with low-loss fittings and are set for direct and straight line-set access to the home
- Liquid line filter drier protects every unit
- Charged for 15 feet of line-set
- All models ETL-, ETLC-, and ARI-listed



**CONCORD**  
Quality heating and cooling products

421 Monroe St. • Bellevue, Ohio 44811  
www.concord-air.com



R2AC13B/L-300 (10/05)

© Copyright 2005

*Due to our policy of continuous improvement, specifications are subject to change without notice.*

Printed in U.S.A.